

GI Earthing Strip



MANUFACTURING OF EARTHING ELECTRODE | PURE COPPER | COPPER BONDING ROD |
EARTH FILL COMPOUND | LIGHTNING PROTECTION SYSTEM | EARTH PIT CHAMBER

GI Earthing Strip

Hot Dip Galvanized Steel Strips are manufactured in different dimensions with an average Zinc coating of 70 to 80 microns for Earthing and Lightning Protection Applications.

Features

Available in Coils for Ease of Transportation High quality as each strip is Hot Dipped Individually compared to Commercially manufactured strips as they are dipped in bulk Holes and other fabrications are done prior to Hot Dipping and no part of base metal will be exposed.



Specifications	Details
Base Material	Mild Steel
Coating Material	Zinc
Coating Thickness	Above 70 Microns (avg.)
Avilable Strip Dimension	25x3mm, 25x6mm
	32x6mm, 50x6mm
Lengh	5.5m to 10.0m



- Designed and Manufacture By -

EARTHWAY TECHNOLOGIES LLP

Mfd Upit: - Plot No. A-30, Wadad Layout, In front of NH06 Express Hwy,
Near MIDC, Amravati - 444 701 Maharashtra, IND

Mob - 08408020303

Emails – earthwaytllp@gmail.com, info@earthwaytechnologies.com

www.earthwaytechnologies.com